

	ORIGINAL Quartz Deck with Seam	GRAND LUXURY One Piece Quartz Deck
THERMOMASSEUR® BATH	\$	\$
TUB	\$	\$

THERMOMASSEUR (TMU)		
Jets	37	
1 heated backrest	included	
MiaPlus® Control (uninstalled)	included	
Geysair®	included	
AromaCloud®	N/A	
Chromatherapy	\$	

TUB no therapy	
Chromatherapy	\$
WarmTouchShell [®]	\$
DOT control	included with therapy

FEATURES				
Installation			Drop-in or Alco	ve (3 walls)
No. of bathers	•	Imp. gallo	ons	42
US gallons	50	Integrated	d waste & overflow	inst. & incl.
INTEGRATED WASTE & OVERFLOW				
Chrome, White				
Brass, Brushed Nickel, Polished Nickel				
COLOR (INNER SHELL) DECK	COLOR		
Standard White	Standa Grey	Noka	Jet Lago	os.

OPTIONAL UPCHARGE APPLICABLE			
FINISH (INNER SHELL)			
UltraVelour Matte Finish (White Only)	\$		
QUARTZ COLOR			
Optional color Quasar Piatra Light Grey Emperadoro Tuscan Dawn Maximus	\$		
QUARTZ SKIRT	MONARCH SKIRT 6018		
Quartz Skirt Color	\$		
CONTROL (TMU ONLY)			
MiaMulti®(uninstalled)	\$		
WASTE & OVERFLOW (16" X 35")			
Chrome	\$		
White	\$		
Brass	\$		
Brushed nickel, Polished nickel & Oil-rubbed bronze	\$		
TILE FLANGE (specify left or right)			
Ordered with bath, uninstalled	\$		
Factory installed	\$		



DON'T FORGET THAT THIS MODEL IS AVAILABLE IN **WHITE ONLY WITH CHOICE OF DECK COLOR.** DON'T FORGET TO SPECIFY **THE FINISH OF THE INTEGRATED WASTE & OVERFLOW.**




MONARCH 6031 60" X 31" X 20"


ACCESSORIES


OTHER Control cannot be installed on the quartz deck.

TOTAL PRICE

DROP-IN/ALCOVE INSTALLATION







LETTER	DESCRIPTION	MEASURE
A	Total length	60"
В	Total width	31"
С	Bathing well length (at height of jets)	43 5/8"
D	Bathing well width (at height of jets)	19 5/8"
E	Deck width (edges)	4"
F	Deck width (sides)	4 1/8"
G	Tub height	19 7/8"
Н	Height from waste to center of overflow	15 3/8"
I	Outside edge to center waste	11 1/8"
J	Slope of backrest	24°
K	Quartz deck height	3/4"

Indicates turbine position (TMU) Indicates WarmTouchShell position (TUB) Indicates LED light position

\$

Indicates heated backrest (TMU)

			_
1			
Н	1	i /	
	Ŭ		

TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.		
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option , a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI.		

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

Approx. shipping weight	230 lbs
Turbine power	600 W
Air heater	600 W

WARRANTY			
Controls-LED-Geysair*	5 years		
Quartz Deck*	15 years		
Bath & turbine*	20 years		

*Some restrictions apply | www.bainultra.com/warranty





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.