

### Product No.

Model	TMU BMEFRIOOT-XX	Soaker BMEFRIOON-XX

# ThermoMasseur (TMU)

Air Jet System	\$5,045	
Jets	40	
1 heated backrest	Included	
MiaPlus® Control	Included	
BU-Touch Control Application BUTOUCH	\$495	
Geysair®	Included	
AromaCloud®** BAROMAC	\$590	
Illuzio Chromatherapy BCHRO6	\$995	

Soaker	\$2,190
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy

### **Features**

Installation Type	Drop-in, Undermount & Alcove (3 walls)
No. of bathers 🕴 Imp. gallons 38 US gallons 45	
Standard Bath Color	
White 01 Biscuit 02	Included

#### **Options** UPCHARGE APPLICABLE

Skirt	BSMUL-XX	Multifit BSJ1-XX	SJ-1
○ White 01 ○ Biscuit 02		\$695	\$715
Tile Flange (specify right or left)			
Ordered with bath (not installed) BTILEN		\$79	
Factory-installed. Right BTILER, Left BTILEL Special installation BTILEO	,	\$155	
Bath Pillow BPILLOW		\$240	
Comfort Cushion BCUSHIONA		\$540	
■ Grey 05 ■ Black 02			
Drain & Overflow		Integrated ZenFlow <sup>†</sup> BOVERINZF-XX	16" x 35" BOVER16-XX
Chrome 07		\$205	\$260
◯ White 01 ◯ Biscuit 02		\$165	\$290
Brushed Nickel 09		\$205	\$290
Polished Nickel 10		\$205	\$290
Oil-rubbed Bronze 11		N/A	\$400
■ Matte Black 19 ■ Satin Brass 18		\$260	N/A
If Required by Construction Code			
16" x 35" Cable driven brass drain & overflow	kit BOVERBR	\$240	
Brass drain & overflow kit‡ BDRCOB		\$240	
Brass drain kit‡ BDRCB		\$60	




https://bainultra.com/sites/default/files/product\_files/product\_sheet-meridian-50.pdf

ZenFlow: Integrated overflow without a trim.
When ordered with Integrated drain & overflow.
The AromaCloud® is built into the deck (factory installed).
Not available for undermount installation.





# **Technical Specifications**



Letter	Description	Measure
A	Outside edge to center drain	10 %"
В	Outside edge to overflow	4 1/8"
С	Total length	60"
D	Total width	36 1/2"
E	Bathing well length	42 3/8"
F	Bathing well width	22 3/4"
G	Deck width	4 1/4"
Н	Deck width at backrest end	4"
I	Height from bottom of bath to top deck	20 1/4"
J	Height from bottom of bath to bottom of deck	18 3/4"
K	Height from bottom of drain to center of overflow	16"
L	Maximum water level (Drain & overflow 16" x 35")	14 1/4"
М	Slope of backrest	24°

● Turbine position (TMU) ● Indicates heated backrest (TMU) 
⑤ Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.	
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).	
	Optional Tile Flange (specify right or left). When ordered with a factory-installed tile flange, the control will not be installed on the bath.	

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 9000006
Approx. shipping weight	124 lb
Turbine power	550 W
Air heater	600 W

## Warranty

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

<sup>\*</sup> Some restrictions apply | www.bainultra.com/warranty