

PRODUCT SHEET

CITTI 6032 WITH INSERT

60" X 32" X 20"



THERMOMASSEUR® BATH	\$
TUB	\$


THERMOMASSEUR (TMU)	
Jets	42
1 heated backrest	included
Mia® Control	included
Geysair®	included
AromaCloud®	\$
Illuzio Chromatherapy NEW	\$


TUB (soaker)	
AromaCloud®	\$
Illuzio Chromatherapy NEW	\$
WarmTouchShell®	\$
DOT control	included with therapy

FEATURES			
Installation type	Alcove (3 walls)		
No. of bathers	↓	Integrated waste & overflow	inst. & incl.
US gallons	50	Integrated skirt & tile flange (specify right or left)	inst. & incl.
Imp. gallons	42		

INTEGRATED WASTE & OVERFLOW	
Chrome, White	
Brass, Brushed Nickel, Polished Nickel	

OPTIONAL UPCHARGE APPLICABLE

COLOR	
Standard	
 White	 Biscuit
Optional	
 Gray	\$
FINISH	
UltraVelour Matte Finish (White Only)	\$
CONTROL (TMU ONLY)	
MiaPlus®*	\$
MiaMulti®	\$

 TURBINE MUST BE REMOTELY INSTALLED. WITH THE AROMACLOUD AND/OR CONTROL ON THE DECK, A COMPLETE SHOWER DOOR CANNOT BE INSTALLED.
DON'T FORGET TO SPECIFY THE FINISH OF THE INTEGRATED WASTE & OVERFLOW.
 * THE MIAPLUS CONTROL IS INCLUDED WHEN PURCHASING CHROMATHERAPY ON A TMU.

1 800 463.2187 
 info@bainultra.com

From 8 a.m. to 8 p.m. Monday to Thursday (EST)
 From 8 a.m. to 5 p.m. on Friday (EST)



 The quest for your wellness®
 www.bainultra.com

CITTI 6032 WITH INSERT 60" X 32" X 20"

ACCESSORIES (OPTIONAL)


OTHERS	<ul style="list-style-type: none"> - The turbine must be remotely installed. - Citti bathtubs include an integrated tile flange, specify left or right. - Insert can be installed on right or left side.
TOTAL PRICE	\$

ALCOVE INSTALLATION



LETTER	DESCRIPTION	MEASURE
A	Outside edge to center drain	10 7/8"
B	Outside edge to centre of waste hole	2 3/4"
C	Total length	60"
D	Total width	32"
E	Bathing well length	49 1/4"
EE	Bathing well length - insert side	41 5/8"
F	Bathing well width	21 1/8"
G	Deck width	3 3/4"
H	Deck width at waste end	2"
I	Height from bottom of tub to top deck	20"
J	Height from drain to center of overflow	14 1/2"
K	Slope of backrest	17°
L	Deck width overflow side	2 1/8"

- A** AromaCloud position
- B** Control position when factory-installed (Mia or Dot)
- Heated backrest (TMU)
- WarmTouchShell position



TECHNICAL SPECIFICATIONS

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". Standard connection is 20 A, 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A, 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

Approx. shipping weight	125 lbs
Turbine power	550 W
Air heater	600 W

WARRANTY

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

*Some restrictions apply | www.bainultra.com/warranty



The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0,64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.