



PRODUCT SHEET **INUA** 6036 60" x 36" x 23"



| THERMOMASSEUR® BATH | \$ |
|---------------------|----|
| TUB | \$ |

| THERMOMASSEUR (TMU) | | |
|---------------------------|----------|--|
| Jets | 46 | |
| 1 heated backrest | included | |
| MiaPlus® Control | included | |
| Geysair® | included | |
| AromaCloud® | \$ | |
| Illuzio Chromatherapy NEW | \$ | |

| TUB (soaker) | | |
|---------------------------------|-----------------------|--|
| AromaCloud® | \$ | |
| Illuzio Chromatherapy NEW | \$ | |
| WarmTouchShell® | \$ | |
| DOT control (standard location) | included with therapy | |

| FEATURES | | | |
|-------------------|----------|------------------------------|---------|
| Installation type | | | Drop-in |
| No. of bathers | * | Inverted V | 1 |
| US gallons | 54 | Armrests | 2 |
| Imp. gallons | 45 | Grab bars (color match) | 2 |
| Raised seat | 1 | Comfort cushion (gray/black) | 1 |

| OPTIONAL UPCHARGE APP | LICABLE | |
|--|-----------|--------------------------------|
| COLOR | | |
| Standard White Biscuit | | |
| Optional Gray | | \$ |
| FINISH | | |
| UltraVelour Matte Finish (White Only) | | \$ |
| CONTROL (TMU ONLY) | | |
| MiaMulti® | | \$ |
| CLEAR ACRYLIC GRAB BAR | S | |
| With Chrome, Brass or Brushed nickel inserts | | \$ |
| WASTE & OVERFLOW | 16" x 35" | INTEGRATED WASTE & OVERFLOW |
| White | \$ | \$ |
| Biscuit | \$ | \$ |
| Chrome | \$ | \$ |
| Brass | \$ | \$ |
| Brushed & Polished nickel | \$ | \$ |
| Oil-rubbed bronze | \$ | N/A |

Standard Deck

SPECIFY THE COMFORT CUSHION COLOR: WARM GRAY OR BLACK. DON'T FORGET TO SPECIFY THE DECK HEIGHT (1/2" OR 11/2").



1 800 463.2187 **9** info@bainultra.com

Image: State of the state of


INUA 6036 60" x 36" x 23"


THERAPEUTIC COMFORT CUSHION - INCLUDED


- Their ultraresistant urethane gel construction makes them:
- Extremely comfortable and soft to the touch
- Fully waterproof - Remarkably durable
- Color available: Warm Gray + Black

DROP-IN INSTALLATION

With the AromaCloud, you must choose to install the control or the faucet on opposite side.







TOTAL PRICE

| LETT | TER DESCRIPTION | MEASUR |
|------|---|--------------|
| A | Outside edge to center drain | 11 1/4'' |
| в | Outside edge to overflow | 4 1/2'' |
| с | Total length | 60'' |
| D | Total width | 36" |
| Е | Bathing well length | 42 1/4" |
| F | Bathing well width at foot area | 23" |
| G | Raised seat length | 20 1/8'' |
| н | Deck width at backrest end | 4 1/8'' |
| I | Deck width at drain end | 4 1/8'' |
| J | Deck width | 4" |
| к | Height from bottom of tub to top deck | 23" |
| L | Total height to headrest | 21" |
| м | Height from bottom of tub to bottom of lip (std. de | ck) 19 1/2'' |
| M' | Height from bottom of tub to bottom of lip (slim de | eck) 20 1/2" |
| N | Height from drain to center of overflow | 17 1/8" |
| 0 | Maximum water level | 15 3/8" |
| Р | Slope of backrest | 24º |
| Q | Minimum spout reach | 8" |
| R | Slim deck minimum height | 1/2" |
| s | Standard deck minimum height | 1 1/2'' |

AromaCloud position

Heated backrest (TMU) Control position when factory-installed (Mia or Dot) 🔘 WarmTouchShell position

Turbine position (TMU)

TECHNICAL SPECIFICATIONS

| Hot water supply required | Should be 70% of water capacity of tub or greater. | |
|------------------------------|---|--|
| Turbine | Access to the pump must be at least 18" X 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option , a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" X 4" minimum | |

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.

| Approx. shipping weight | 137 lbs |
|-------------------------|---------|
| Turbine power | 550 W |
| Air heater | 600 W |

WARRANTY

| Controls-LED-Geysair* | 5 years |
|-----------------------|----------|
| Bath & turbine* | 20 years |

*Some restrictions apply | www.bainultra.com/warranty



\$