

	ORIGINAL Quartz Deck with Seam	GRAND LUXURY One Piece Quartz Deck
THERMOMASSEUR® BATH	\$	\$
TUB	\$	\$

THERMOMASSEUR (TMU)		
Jets	42	
1 heated backrest	included	
MiaPlus® Control (uninstalled)	included	
Geysair®	included	
AromaCloud <sup>®</sup>	N/A	
Illuzio Chromatherapy <b>NEW</b>	\$	
2 <sup>nd</sup> heated backrest	\$	

TUB (soaker)	
Illuzio Chromatherapy <b>NEW</b>	\$
WarmTouchShell®	\$
OOT control included with the	
2 <sup>nd</sup> WarmTouchShell®	\$

FEATURES			
Installation		Drop-in or Alco	ve (3 walls)
No. of bathers	**	Imp. gallons	42
US gallons	50	Integrated waste & overflow	inst. & incl.
INTEGRATED WASTE & OVERFLOW			

INTEGRATED WASTE & OVERFLOW	

Chrome, White Brass, Brushed Nickel, Polished Nickel


COLOR (INNER SHELL)	QUARTZ DECK COLOR
---------------------	-------------------

Stan	Standard		
White	_		

Standa	rd	
	7000	
Grey	Noka	Jet
хро		Black



OPTIONAL UPCHARGE APPLICABLE		
FINISH (INNER SHELL)		
UltraVelour Matte Finish (White Only)	\$	
DECK COLOR		
Optional color  Quasar Piatra Bianco Woodlands Statuario Maximus	\$	
QUARTZ SKIRT	MONARCH SKIRT 6618	
Quartz Skirt Color (for all quartz finishes)	\$	
CONTROL (TMU ONLY)		
MiaMulti®(uninstalled)	\$	
WASTE & OVERFLOW (16" X 35")		
Chrome	\$	
White	\$	
Brass	\$	
Brushed nickel, Polished nickel & Oil-rubbed bronze	\$	
TILE FLANGE (specify front or back)		
Ordered with bath, uninstalled	\$	
Factory installed	\$	





## MONARCH 6636 66" X 36" X 20"


## **ACCESSORIES (OPTIONAL)**

**OTHER** Control cannot be installed on the quartz deck.

TOTAL PRICE

\$

## DROP-IN/ALCOVE INSTALLATION





LETTER	DESCRIPTION	MEASURE
Α	Total length	66"
В	Total width	36"
С	Bathing well length (at height of jets)	46 1/8"
D	Bathing well width (at height of jets)	23 1/4"
E	Deck width (edges)	4 3/4"
F	Deck width (sides)	4 5/8"
G	Tub height	19 5/8"
Н	Height from waste to center of overflow	15 1/2"
I	Outside edge to center waste	11 3/8"
J	Slope of backrest	23°
K	Quartz deck height	3/4"

Turbine position (TMU)

Heated backrest (TMU)

■ WarmTouchShell position





## **TECHNICAL SPECIFICATIONS**

Hot water supply required	Should be 70% of water capacity of tub or greater.
Turbine	Access to the pump must be at least 18" X 22". <b>Standard connection is 20 A. 120 V, 60 hz</b> , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). <b>For any additional option</b> , <b>a second line is needed 15 A. 120 V, 60 hz</b> , dedicated line with a GFCI.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/documentation/documentation).

Approx. shipping weight	253 lbs
Turbine power	550 W
Air heater	600 W

WARRANTY	
Controls-LED-Geysair*	5 years
Quartz Deck*	15 years
Bath & turbine*	20 years

\*Some restrictions apply | www.bainultra.com/warranty





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4"  $[0.64\ cm]$  variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.