## Freestanding 72" x 40" x 24"

# sanos 7240



### Product No.

Model Flat deck	TMU BBSUOFNOT-XX	Soaker BBSUOFNON-XX
Model Rolled deck	TMU BBSUOFPOT-XX	Soaker BBSUOFPON-XX

## ThermoMasseur (TMU)

Air Jet System	\$10,560
Jets	40
1 heated backrest	Included
MiaPlus® Control*	Included
BU-Touch Control Application BUTOUCH	Included
Geysair®	Included
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$7,925
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

## **Features**

. catalog				
Installation Type			Freestanding	
No. of bathers 👬	Imp.gallons 49	US gallons 59		
Standard Bath Co	lor p.17			
○ White 01 ○	Biscuit 02		Included	

1800 463-2187

## **Options** UPCHARGE APPLICABLE

•	
Universal Armrests BGBGU-XX p.16	
White 01	\$895
For Air Supply Only	
Decorative pipe (1 ½" x 6")	\$55
Decorative pipe (11/2" x 24")	\$200
Pipe concealer (3" x 5 1/4")	\$105
Elbow (45°)	\$80
Elbow (90°)	\$105
Bath Pillow BPILLOW p.252	\$240
Comfort Cushion (with flat deck only) BCUSHIONA p.253	\$540
Grey 05  Black 06	
Drain & Overflow p.14	D13 BOVERD13-XX
Chrome 07	\$500
Brushed Nickel 09	\$500
Polished Nickel 10	\$500
Unplated 00	\$500
Oil-rubbed Bronze 11	\$500

Don't forget to indicate flat or rolled deck.





For TMU, control must be wall-mounted. Faucets must be freestanding or wall-mounted.
 The AromaCloud® is built into the deck (factory installed).


## sanos 7240







### **Technical Specifications**



Letter	Description	Measure
A	Outside edge to center drain	11 3/4"
В	Outside edge to overflow	4 3/8"
С	Total length	72"
D	Total width	40"
E	Bathing well length	46 1/8"
F	Bathing well width	24 3/4"
G	Deck width	4 5/8"
Н	Flat surface width	3 %"
I	Rolled deck width	5 3/8"
J	Height from bottom of lip to top deck	2 1/2"
K	Height from bottom of bath to top deck	25 ½"
L	Height from bottom of bath to top deck	24 ½"
M	Height from bottom of drain to center of overflow	16 5/8"
N	Maximum water level	14 %"
0	Slope of backrests	27°
Р	Base length	55 1/8"
Q	Base width	27 1/8"
R	Center drain to center air intake	5"
	aCloud® position ● Indicates heated backrest (TMU ates WarmTouchShell® position (Soaker)	)

The hot water supply required

The hot water supply should be 70% or more of the bath's total water capacity.

Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.

Others

The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access).

There is a height difference for the rolled deck (see drawing Detail A). Faucets must be freestanding or wall-mounted. The turbine must be remotely installed. TMU: Control must be wall-mounted. Soaker: DOT Controls are located on either sides of the AromaCloud® (see page 9, position of DOT Control).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 9000001
Approx. shipping weight	260 lb
Turbine power	550 W
Air heater	600 W

#### Warranty

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

<sup>\*</sup> Some restrictions apply | www.bainultra.com/warranty