CITTI 6032 WITH INSERT

60" x 32" x 20"

Citti® is derived from sanskrit for "free spirit." At the same time, the name evokes today's great cities: these are the perfect baths for urban living.



MODEL	тми	TUB
Left	BCIDRAJLT-XX	BCIDRAJLN-XX
Right	BCIDRAJRT-XX	BCIDRAJRN-XX

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$
Jets	42
1 heated backrest	Included
Mia® Control	Included
BU-Touch Control Application BUTOUCH	\$
Geysair®	Included
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$

TUB Soaker	\$
AromaCloud® BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy

FEATURES					
Installation type	Installation type Integrated skirt & tile flange (specify right or left)			Alcove (3 walls)	
Integrated skirt & tile flar				Installed & Included	
No. of bathers	*	Imp. gallo	ns	42	
US gallons	50				
INTEGRATED WASTE & OVERFLOW BOVERINI-XX					
White 01, Biscuit 02, Chrome 07, Brushed Nickel 09, Polished Nickel 10			Installed & Included		
STANDARD COLOR					
White 01 Biscuit 02				Included	

OPTIONS (UPCHARGE APPLICABLE)		
FINISH		
UltraVelour Matte Finish (White only) BVEL	\$	
INTEGRATED WASTE & OVERFLOW BOVERINI-XX		
Matte Black 19, Satin Brass 18	\$	
CONTROL (TMU only)		
MiaPlus®* BMIAP2-XX	\$	

Turbine must be remotely installed. With the AromaCloud® and/or Control on the deck, a complete shower door cannot be installed. Faucets must be wall-mounted.


Don't forget to specify the **finish of the integrated waste & overflow.**

* The MiaPlus® Control is included when purchasing Chromatherapy on a TMU.

TOTAL PRICE










INSTALLATION



LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	10 7/8"
В	Total length	60"
С	Total width	32"
D	Bathing well length	49 1/4"
DD	Bathing well length - insert side	42 5/8"
E	Bathing well width	21 1/8"
F	Deck width (Skirt side)	3 3/4"
G	Deck width at drain end	2 1/8"
н	Height from bottom of bath to top deck	20"
I	Height from drain to center of overflow	14 1/2"
J	Slope of backrest	17°
К	Deck width overflow side	2 1/8"
L	Outside edge to center drain	15 1/8"
М	Tile flange height	1"

A AromaCloud® position

ⓒ Control position when factory-installed (Mia® or DOT)

Indicates heated backrest (TMU)

Indicates WarmTouchShell® position (TUB)

Hot water supply required	Should be 70% of water capacity of TUB or greater.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 hz , dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 hz , dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The GEYSAIR must always be accessible and connected to the hot water supply (provide access) The turbine must be remotely installed. Citti bathtubs include an integrated tile flange, specify right or left. Insert can be installed on right or left side.

Approx. shipping weight	125 lbs	
Turbine power	550 W	
Air heater	600 W	
WARRANTY		
Controls-LED-Geysair*	5 years	
Bath & turbine*	20 years	

 $[\]mbox{\tt *}$ Some restrictions apply | www.bainultra.com/warranty





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.