elegancia 6636

66" x 36" x 21"



Product No.

Model C10	TMU BELLRDAOT-XX	Soaker BELLRDAON-XX
Model C11	TMU BELLODBOT-XX	Soaker BELLODBON-XX

Model C13	TMU BELLODDOT-XX	Soaker BELLODDON-XX
Model C14	TMU BELLODEOT-XX	Soaker BELLODEON-XX

ThermoMasseur (TMU)

Air Jet System	\$6,330
Jets	36
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$495
Geysair®	Included
AromaCloud® BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$3,135
AromaCloud® BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

Options UPCHARGE APPLICABLE

Grab Bars p.16	Clear Acrylic [∞] BGBG10-XX	
Chrome 07	\$60	
Brushed Nickel 09	\$60	
Bath Pillow BPILLOW p.252	\$240	
Comfort Cushion BCUSHIONA p.253	\$540	
■ Grey 05 ■ Black 06		
Drain & Overflow p.14	D13 BOVERD13-XX	D14 ⁺⁺⁺ BOVERD14-XX
Chrome 07	\$500	\$270
White 01	N/A	\$270
Biscuit 02	N/A	\$270
Brushed Nickel 09	\$500	\$270
Polished Nickel 10	\$500	\$270
Oil-rubbed Bronze 11	\$500	\$270
Matte Black 19 Satin Brass 18	N/A	N/A
Unplated 00	\$500	N/A

Features

Installation Type	Drop-in
No. of bathers 👬 Imp. gallons 38 US gallons 46 Armrests 4 Grab bars (color match) 2	
Standard Bath Color p.17	
White 01 Biscuit 02	Included

Don't forget to select a contour among the 4 available to choose from.



2025 1800 463-2187


 [†] ZenFlow: Integrated overflow without a trim.
 [⋄] Specify insert finish. With Chrome or Brushed Nickel inserts.
 ^{‡‡†} Piping is not included for the drain & overflow D14.

elegancia 6636






Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11 ½"
В	Outside edge to overflow	5 ½"
С	Total length	66"
D	Total width	36"
E	Bathing well length	42"
F	Bathing well width	21 3/8"
G	Deck width (widest point)	51/4"
Н	Deck width at backrest end	4 3/4"
I	Height from bottom of drain to center of overflow	16"
J	Maximum water level (Drain & overflow 16" x 35")	14 5/16"
K	Slope of backrests	30°

- ♠ AromaCloud® position
 ♠ Control position when factory-installed (Mia® or DOT)
 ♠ Turbine position (TMU)
 ♠ Indicates heated backrest (TMU)
 ♠ Indicates WarmTouchShell® position (Soaker)

Choose Your Contour



Letter	М	N	0
Description	Deck width (Narrowest point)	Height from bottom of bath to top deck	Height from bottom of bath to bottom of deck
C10	3 1/4"	20 ¾"	18 1/4"
C11	3 1/2"	20 5/8"	17 5/8"
C13	3 5/8"	20 %"	18 5/8"
C14	3 1/4"	20 3/4"	18 1⁄4"

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access).

provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 9000044 (C11, C13 & C14)
Approx. shipping weight	135 lb
Turbine power	550 W
Air heater	600 W

Warranty

,	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*}Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ± 0.25 " (± 0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.