meridian 6032

60" × 32" × 21"



Product No.

Model Alcove, Right	TMU BMEDRIORT-XX	Soaker BMEDRIORN-XX
Model Alcove, Left	TMU BMEDRIOLT-XX	Soaker BMEDRIOLN-XX
Model Drop-in	TMU BMEDRIOOT-XX	Soaker BMEDRIOON-XX

ThermoMasseur (TMU)

Air Jet System	\$4,885
Jets	37
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$495
Geysair®	Included
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995

Soaker	\$1,900
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy

Features

Installation Type	Drop-in, Undermount & Alcove (3 walls))	
No. of bathers 🕴 Imp. gallons 41 US gallons 50		
Integrated Tile Flange (specify right or left)	Included	
Standard Bath Color		
White 01 Biscuit 02	Included	

1800463-2187

Options UPCHARGE APPLICABLE

Skirt	BSMUL-XX	Multifit BSJ1-XX	SJ-1
○ White 01 ○ Biscuit 02		\$695	\$715
Bath Pillow BPILLOW		\$240	
Comfort Cushion BCUSHIONA		\$540	
Grey 05 Black 02			
Drain & Overflow		Integrated ZenFlow [†] BOVERINZF-XX	16" x 35" BOVER16-XX
Chrome 07		\$205	\$260
○ White 01 ○ Biscuit 02		\$165	\$290
Brushed Nickel 09		\$205	\$290
Polished Nickel 10		\$205	\$290
Oil-rubbed Bronze 11		N/A	\$400
■ Matte Black 19 ■ Satin Brass 18		\$260	N/A
If Required by Construction Code			
16" x 35" Cable driven brass drain & overflow	kit BOVERBR	\$240	
Brass drain & overflow kit‡ BDRCOB		\$240	
Brass drain kit‡ BDRCB		\$60	



https://bainultra.com/sites/default/files/product_files/product_sheet-meridian-6032.pdf


ZenFlow: Integrated overflow without a trim.
When ordered with Integrated drain & overflow.
The AromaCloud® is built into the deck (factory installed).
Not available for undermount installation.

meridian 6032





Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11"
В	Outside edge to overflow	4"
С	Total length	60"
D	Total width	32"
E	Bathing well length	43 5/8"
F	Bathing well width	19 5/8"
G	Deck width	4 1/4"
Н	Deck width at drain end	3 ½"
I	Height from bottom of bath to top deck	20 ½"
J	Height from bottom of bath to bottom of deck	19"
K	Height from bottom of bath to top of tile flange	21 1/2"
L	Tile flange height	1"
M	Height from bottom of drain to center of overflow	15 ¹³ /16"
N	Maximum water level (Drain & overflow 16" x 35")	14 1/16"
0	Slope of backrest	24°
 ♠ AromaCloud® position ♠ Control position when factory-installed (Mia® or DOT) ♠ Turbine position (TMU) ♠ Indicates heated backrest (TMU) ♠ Indicates WarmTouchShell® position (Soaker) 		

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access).
	There is a height difference for the integrated tile flange (see Detail A).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000053
Approx. shipping weight	100 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*} Some restrictions apply | www.bainultra.com/warranty