meridian ellipse 6636

66" x 36" x 21"



Product No.

Model Rolled deck	TMU BMELOUMOT-XX	Soaker BMELOUMON-XX
Model Flat deck	TMU BMELOUNOT-XX	Soaker BMELOUNON-XX

ThermoMasseur (TMU)

Air Jet System	\$6,080
Jets	38
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$495
Geysair®	Included
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker	\$2,690
AromaCloud®** BAROMAC	\$590
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

Features

Installation Type			Drop-in	
No. of bathers 👬	Imp. gallons 40	US gallons 48		
Standard Bath Co	lor p.17			
White 01	Biscuit 02		Included	

Options UPCHARGE APPLICABLE

Bath Pillow BPILLOW p.252	\$240
Comfort Cushion BCUSHIONA p.253	\$540
■ Grey 05 ■ Black 02	
Drain & Overflow p.14	16" x 35" BOVER16-XX
Chrome 07	\$260
White 01 Biscuit 02	\$290
Brushed Nickel 09	\$290
Polished Nickel 10	\$290
Oil-rubbed Bronze 11	\$400
Matte Black 19 Satin Brass 18	N/A
If Required by Construction Code	
16" x 35" Cable driven brass drain & overflow kit BOVERBR	\$240



https://bainultra.com/sites/default/files/product_files/product-sheet-meridian-ellipse-6636.pdf

Don't forget to indicate flat or rolled deck.

^{**} The AromaCloud® is built into the deck (factory installed).


meridian ellipse 6636







Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11 ½"
В	Outside edge to overflow	4 5/8"
С	Total length	66"
D	Total width	36"
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width at backrest end	4 3/8"
Н	Flat surface width	4 1/4"
I	Rolled deck width	4 3/4"
J	Height from bottom of bath to top deck	21"
K	Height from bottom of bath to top deck	22"
L	Height from bottom of bath to bottom of deck	19 ½"
М	Height from bottom of deck to top deck	21/2"
N	Height from bottom of drain to center of overflow	16 %"
0	Maximum water level (Drain & overflow 16" x 35")	14 7/8"
P	Slope of backrest	25°
Turbir	aCloud® position	

Hot water supply required

The hot water supply should be 70% or more of the bath's total water capacity.

Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.

Others

The Geysair® is located on the same side as the heated backrest. It must not be relocated.

It must be connected to the hot water supply and be accessible (provide access).

There is a height difference for the rolled deck (see drawing Detail A).

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000055
Approx. shipping weight	100 lb
Turbine power	550 W
Air heater	600 W

Warranty

•	
Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

^{*} Some restrictions apply | www.bainultra.com/warranty