

origami 7236

72" × 36" × 22"



Product No.

Model 4" deck	TMU BOOSRI00T-XX	Soaker BOOSRI00N-XX
Model 2" deck	TMU BOOSRI20T-XX	Soaker BOOSRI20N-XX
Model Slim deck ½"	TMU BOOSRI10T-XX	Soaker BOOSRI10N-XX

ThermoMasseur (TMU)

Air Jet System	\$6,700
Jets	42
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH	\$495
Geysair®	Included
AromaCloud®** BAROMAC	\$590
AromaFlow†† BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
2nd heated backrest (WTS-1 zone) BSHB	\$1,125

Soaker

AromaCloud®** BAROMAC	\$590
AromaFlow†† BAROMAF	\$950
Illuzio Chromatherapy BCHRO6	\$995
WarmTouchShell® BWTS	\$1,125
DOT Control	Included with therapy
2nd WarmTouchShell® BWTS2	\$370

Features

Installation Type	Drop-in: ½", 2" & 4", Alcove (3 walls): 2" & Undermount: ½"
No. of bathers 2 2 Imp. gallons 54 US gallons 64	
Standard Bath Color	
White 01 Biscuit 02	Included

Options UPCHARGE APPLICABLE

Finish			
UltraVelour Matte Finish (white only) BVEL1		\$650	
Universal Armrests BGBGU-XX			
White 01		\$895	
Skirt (2" deck only)	Multifit BSMUL-XX	SJ-1 BSJ1-XX	
White 01 Biscuit 02		\$695	\$715
Tile Flange (with 2" deck only) (specify front or back)			
Ordered with bath (not installed) BTILEN		\$79	
Factory-installed. Front BTILEF, Back BTILEB, Special installation BTILEO		\$155	
Bath Pillow BPILLOW		\$240	
Drain & Overflow	Integrated ZenFlow† BOVERINZF-XX	Integrated with trim BOVERIN-XX	16" x 35" BOVER16-XX
Chrome 07	\$205	\$235	\$260
White 01 Biscuit 02	\$165	\$205	\$290
Brushed Nickel 09	\$205	\$235	\$290
Polished Nickel 10	\$205	\$235	\$290
Oil-rubbed Bronze 11	N/A	N/A	\$400
Matte Black 19 Satin Brass 18	\$260	\$290	N/A
Matte White 32	\$205	\$235	N/A
If Required by Construction Code			
Brass drain & overflow kit † BDRCOB		\$240	
Brass drain kit † BDRCB		\$60	
16" x 35" Cable driven brass drain & overflow kit BOVERBR		\$240	

⚠ Don't forget to indicate the deck height (½", 2" or 4").

½" slim deck is available for drop-in and undermount installation only.


† ZenFlow: Integrated overflow without a trim.
** The AromaCloud® is built into the deck (factory installed). Not available for undermount installation.
‡ When ordered with Integrated drain & overflow.
†† When ordering an AromaFlow, a ZenFlow is mandatory (Upcharge). Specify the finish of the drain.

origami 7236

72" × 36" × 22"



Technical Specifications



Letter	Description	Measure
A	Outside edge to center drain	11 1/4"
B	Outside edge to overflow	4 5/8"
C	Total length (with slim deck height) Total length (with 2" deck height) Total length (with 4" deck height)	71 1/4" 71 5/8" 72"
D	Total width (with slim deck height) Total width (with 2" deck height) Total width (with 4" deck height)	35 1/4" 35 5/8" 36"
E	Bathing well length	48 1/8"
F	Bathing well width	22"
G	Deck width	4 3/8"
H	Deck width at backrest ends	1 3/4"
I	Height from bottom of deck to top deck	1/2"
J	Height from bottom of deck to top deck	2"
K	Height from bottom of deck to top deck	4"
L	Height from bottom of bath to top deck	22"
M	Height from bottom of drain to center of overflow	17 3/4"
N	Maximum water level (Drain & overflow 16" x 35") Maximum water level (Integrated drain & overflow) Maximum water level with AromaFlow	16" 17" 16 1/2"
O	Slope of backrests	24°

A AromaCloud® position **B** Control position when factory-installed (Mia® or DOT)
T Turbine position (TMU) **H** Indicates heated backrest (TMU)
S Indicates WarmTouchShell® position (Soaker)

Hot water supply required	The hot water supply should be 70% or more of the bath's total water capacity.
Turbine	Access to the pump must be at least 18" x 22". Standard connection is 20 A, 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A, 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.
Others	The Geysair® is located on the same side as the heated backrest. It must not be relocated. It must be connected to the hot water supply and be accessible (provide access). Optional tile flange with 2" deck height only (specify front or back). The water level will vary when an AromaFlow or an Integrated drain & overflow is installed.

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

Cutting template	# 90000101
Approx. shipping weight	137 lb
Turbine power	550 W
Air heater	600 W

Warranty

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years

* Some restrictions apply | www.bainultra.com/warranty

Dimensions are subject to change; measured at external edges. Bathing well measured at air jet level. Tolerance: ±0.25" (±0.64 cm). Ensure bathtub is received prior to any construction. BainUltra® is not responsible for any preparatory work done before product arrival.