

Product No.

| Model | Drop-in Standard 11/2"deck | TMU | BVIBRD00T-XX | Soaker | BVIBRD00N-XX |
|-------|-------------------------------|-----|--------------|--------|--------------|
| Model | Alcove, L Standard 11/2" deck | TMU | BVIBRBOLT-XX | Soaker | BVIBRBOLN-XX |
| Model | Alcove, R Standard 11/2" deck | TMU | BVIBRBORT-XX | Soaker | BVIBRBORN-XX |

| Model Slim deck 1/2" | TMU BVIBRU10T-XX | Soaker BVIBRU10N-XX |
|-----------------------------|------------------|---------------------|
| Model Slim deck, Left 1/2" | TMU BVIBRB1LT-XX | Soaker BVIBRB1LN-XX |
| Model Slim deck, Right 1/2" | TMU BVIBRB1RT-XX | Soaker BVIBRB1RN-XX |

ThermoMasseur (TMU)

| Air Jet System | \$4,895 | | |
|--------------------------------------|----------|--|--|
| Jets | 40 | | |
| 1 heated backrest | Included | | |
| MiaPlus® Control | Included | | |
| BU-Touch Control Application BUTOUCH | \$495 | | |
| Geysair® | Included | | |
| Illuzio Chromatherapy BCHRO6 | \$995 | | |

| Soaker | \$2,435 |
|------------------------------|-----------------------|
| Illuzio Chromatherapy BCHRO6 | \$995 |
| WarmTouchShell® BWTS | \$1,125 |
| DOT Control | Included with therapy |

| Features | |
|--|---|
| Installation Type | Drop-in & Alcove (3 walls): ½",1½" Undermount: ½" |
| No. of bathers 🕴 Imp. gallons 36 US gallon | s 44 Integrated tile flange Included |
| Integrated Drain & Overflow — ZenFlow† B | OVERINIZF-XX |
| White 01 Biscuit 02 | Installed & Included |
| Standard Bath Color p. 17 | |
| White 01 Biscuit 02 | Included |

1800 463-2187

| Ontions | LIDCHADGE | A DDI | ICADI E |
|---------|-----------|-------|---------|
| | | | |

| Options upcharge applicable | | |
|---|--|---------------------------------------|
| Finish | | |
| UltraVelour Matte Finish (white only) BVEL2 | \$650 | |
| Universal Armrests BGBGU-XX | | |
| White 01 | \$895 | |
| Skirt Multifit (standard 11/2" deck only) BSMUL-XX | | |
| ○ White 01 ○ Biscuit 02 | \$695 | |
| Bath Pillow BPILLOW | \$240 | |
| Drain & Overflow | Integrated ZenFlow [†] BOVERINZF-XX | Integrated with trim BOVERIN-XX |
| White 01 Biscuit 02 | Incl. | \$40 |
| Matte White 32 Chrome 07 Brushed Nickel 09 Polished Nickel 10 | \$40 | \$70 |
| Matte Black 19 Satin Brass 18 | \$95 | \$125 |
| If Required by Construction Code | | |
| Brass drain & overflow kit BDRCOB | \$240 | |
| Brass drain kit BDRCB | \$60 | |

Don't forget that an integrated tile flange is available at no extra cost. You must specify drain position (right or left). With the control on the deck, a complete shower door cannot be installed.

Don't forget to specify the finish of the Integrated drain & overflow.
The ½" deck is required for undermount installation.




[†] ZenFlow: Integrated overflow without a trim.

vibe 6030





Technical Specifications



| Letter | Description | Measure |
|--------|--|----------|
| A | Outside edge to center drain | 10 %" |
| В | Outside edge to center of overflow | 2 1/2" |
| С | Total length | 60" |
| D | Total width | 30" |
| E | Bathing well length | 44" |
| F | Bathing well width | 19 1/8" |
| G | Deck width | 1 1/8" |
| Н | Deck width at drain end | 2" |
| I | Height from bottom of bath to top deck | 18 1/2" |
| J | Maximum water level | 14 5/16" |
| K | Slope of backrest | 27° |
| L | Height from bottom of deck to top std deck | 1 1/2" |
| M | Height from bottom of deck to top slim deck | 1/2" |
| N | Tile flange height | 1" |
| 0 | Height of bath from bottom of bath to top of tile flange | 19 ½" |
| 0 | | T |

● Control position when factory-installed (Mia® or DOT) ● Turbine position (TMU) ● Indicates heated backrest (TMU) ⑤ Indicates WarmTouchShell® position (Soaker)

| Hot water supply required | The hot water supply should be 70% or more of the bath's total water capacity. |
|---------------------------|--|
| Turbine | Access to the pump must be at least 18" x 22". Standard connection is 20 A. 120 V, 60 Hz, dedicated line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is needed 15 A. 120 V, 60 Hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum. |
| Others | The Geysair® is located on the same side as the heated backrest. It must not be relocated It must be connected to the hot water supply and be accessible (provide access). |
| | Turbine must be remotely installed in certain conditions. Integrated tile flange is included (specify right or left). |

Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal, provincial/state and local building codes and regulations (www.bainultra.com/dealers/dealer-documentation-and-catalog).

| Cutting template | # 90000106 | |
|-------------------------|------------|--|
| Approx. shipping weight | 200 lb | |
| Turbine power | 550 W | |
| Air heater | 600 W | |

Warranty

| Controls-LED-Geysair* | 5 years |
|-----------------------|----------|
| Bath & turbine* | 20 years |

^{*} Some restrictions apply | www.bainultra.com/warranty