
## **ELLIPSE** 6636

Named after the meridians of our body—the paths along which our energy flows—the collection also brings to mind the meridian (or mid-point) of life with an invitation to relax and listen to your body and mind.



MODEL		тми	TUB	
	Rolled deck	BMELOUM0T-XX	BMELOUM0N-XX	
	Flat deck	BMELOUN0T-XX	BMELOUNON-XX	

THERMOMASSEUR (TMU) Hydro-thermo massage • Air jet system	\$
Jets	38
1 heated backrest	Included
MiaPlus® Control	Included
BU-Touch Control Application BUTOUCH NEW	\$
Geysair®	Included
AromaCloud®* BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
2 <sup>nd</sup> heated backrest (WTS-1 zone) BSHB	\$

<b>TUB</b> Soaker	\$
AromaCloud®* BAROMAC	\$
Illuzio Chromatherapy BCHRO6	\$
WarmTouchShell® BWTS	\$
DOT control	Included with therapy
2 <sup>nd</sup> WarmTouchShell® BWTS2	\$

FEATURES	;			
Installation	Installation type		Drop-in & Undermount**	
No. of bath	ers	* *	Imp. gallons	40
US gallons		48		
STANDAR	D COLOR			
White 01	Biscuit 02			Included

Flat deck

OPTIONS (UPCHARGE APPLICABLE)	
WASTE & OVERFLOW 16" x 35" BOVER16-XX	
Chrome 07	\$
White 01, Biscuit 02	\$
Brushed Nickel 09, Polished Nickel 10, Oil-rubbed Bronze 11	\$
IF REQUIRED BY CONSTRUCTION CODE	
16" x 35" Cable driven brass waste & overflow kit BOVERBR-XX	\$



Don't forget to indicate flat or rolled deck.

\* The AromaCloud® is built into the deck (factory installed).

\*\* The AromaCloud® is not available with Undermount installation.

TOTAL PRICE











## INSTALLATION

For rolled deck: deck modified to host the AromaCloud®





LETTER	DESCRIPTION	MEASURE
Α	Outside edge to center drain	11 1/2"
В	Outside edge to overflow	4 5/8"
С	Total length	66"
D	Total width	36"
E	Bathing well length	42 3/8"
F	Bathing well width	22 1/4"
G	Deck width at backrest end	4 3/8"
н	Flat surface width	4 1/4"
ı	Rolled deck width	4 3/4"
J	Height from bottom of bath to top deck	21"
К	Height from bottom of bath to top deck	22"
L	Height from bottom of bath to bottom of lip	19 1/2"
М	Height from bottom of lip to top deck	2 1/2"
N	Height from drain to center of overflow	16 5/8"
0	Maximum water level	14 7/8"
P	Slope of backrests	25°

- ⚠ AromaCloud® position
- **ⓒ** Control position when factory-installed (Mia® or DOT)
- Turbine position (TMU)
- Indicates heated backrest (TMU)
- Indicates WarmTouchShell® position (TUB)

TECHNICAL SP	PECIFICATIONS	
Hot water supply required	Should be 70% of water capacity of TUB or greater.	Cutting template
supply required	Access to the pump must be at least 18" x 22". <b>Standard connection is 20 A. 120 V, 60 hz</b> , dedicated	Approx. shipping weigh
Turbine	line with a Ground-Fault Circuit Interrupter (GFCI). For any additional option, a second line is	Turbine power
	needed 15 A. 120 V, 60 hz, dedicated line with a GFCI. Air vent necessary: 2" x 4" minimum.	Air heater
Others	<ul> <li>The GEYSAIR must always be accessible and connected to the hot water supply (provide access).</li> <li>There is a height difference for the rolled deck (see drawing Detail A).</li> </ul>	WARRANTY
Our products must be installed by certified professionals only and according to our Owner's Manual as well as federal,		Controls-LED-Geysair*
provincial/state an	d local building codes and regulations (www.bainultra.com/documentation/documentation).	Bath & turbine*

Controls-LED-Geysair*	5 years
Bath & turbine*	20 years
Some restrictions apply I www bainultra co	m/warranty

# 90000055 100 lbs 550 W 600 W





The specifications shown indicate the outer edge dimension and the inside bathing capacity dimension measured at air jets' height. The manufacturer accepts a 1/4" [0.64 cm] variance. There are variations on each product and specifications are subject to change as we improve upon our product as required. The dimensions needed for site preparation and structure building will differ. BainUltra® assumes no responsibility for preparatory work done prior to the product being on site.